

---

# Arrays

IST 256

Application Programming for Information Systems

# Arrays

---

- Give one name to a group of values.
  - In this example, the name of the array is “data” and the values are integers.

data	7
	4
	0
	23
	-5
	14

The elements are numbered starting from 0:

data [ 0 ] (element value is 7)  
data [ 1 ] (is 4)  
data [ 2 ] (is 0)  
...

# Array Declarations

---

type of elements      array name (same rules as other variable names)

*Declaration with allocation*  
String [ ] students = new String [ 25 ];

number of elements

*Declaration (without allocation)*

int [ ] age;

*Another declaration*

double [ ] price = new double [10 ];

*Declaration with initialization*

int [ ] codes = { 4011, 4080, 4549, 4788 }

*(an array with 4 elements )*

# Using elements

---

- Given an array declaration

```
double [ ] amounts = new double [ 25];
```

the valid subscripts to use elements of this array are from 0 to 24 (i.e. from 0 to one less than the number of elements)

- Array elements can be used in expressions

```
tax = amounts[5] * .0825;
```

← Gets the value of amounts[5]

```
amounts[5] = oldprice;
```

← Assigns a new value to amounts[5]

# Loop over all array elements

---

- It is quite common to write a for loop to access every element of an array.
- This can use the length property of the array

*// assigns the numbers from 1 to the array length to the elements*

```
for (int index = 0; index < amounts.length; index++)  
{  
    amounts[index] = index + 1;  
}
```