Parsing: Partial Parsing – Chunking

Partial Parsing

- For many applications you don't really need a full-blown syntactic parse. You just need a good idea of where the base syntactic units are.
 - Often referred to as chunks.
- For example, if you're interested in locating all the people, places and organizations in a text it might be useful to know where all the base noun phrases (NPs) are.
- A partial parse for just base NPs would be:

 $[_{NP} Mr. Vinken]$ is $[_{NP} chairman]$ of $[_{NP} Elsevier N.V.]$, $[_{NP}$ the Dutch publishing group].

Note that base NPs are the noun phrases that do not contain any other noun phrases.

Partial Parsing

• A full partial parse would have chunks for all types of phrases in the text, but with no hierarchical structure:

 $\begin{bmatrix} NP & The morning flight \end{bmatrix} \begin{bmatrix} PP & from \end{bmatrix} \begin{bmatrix} NP & Denver \end{bmatrix} \begin{bmatrix} VP & has arrived \end{bmatrix} \begin{bmatrix} PP & on \end{bmatrix} \begin{bmatrix} NP & time \end{bmatrix}.$

- For complete chunking, typical ordering:
 - Base syntactic phrases
 - Larger verb and noun groups
 - Sentential level rules, e.g. clauses

Rule-Based Partial Parsing

- With the lack of hierarchy between phrases and nesting within phrases (e.g. no NP can be inside another NP), parsing can be rule-based
 - Restrict the form of rules to exclude recursion (make the rules flat).
 - Group and order the rules so that the RHS of the rules can refer to non-terminals introduced in earlier rules but not later ones.
 - Write regular expressions to recognize the right-handside of rules, starting from the later ones.

NLTK Regular Expression Parsing

- Example chunk parser is NLTK's regular expression parser
- Specify chunk phrases by giving regular expression patterns of POS tags
 - Example expression for noun phrases ending in common nouns:
- $NP: \{ <\!\!RB | DT | PP \ | PRP \ >\!\!? <\!\!JJ | JJR | JJS >\!\!* <\!\!VBN | VBG | NNP | CD >\!\!* <\!\!NN | NNS >\!\!+ \}$

Matches noun phrases from the Penn Treebank like:

(NP asbestos/NN)
(NP a/DT fraction/NN)
(NP asbestos-related/JJ diseases/NNS)
(NP large/JJ burlap/NN sacks/NNS)
(NP 33/CD men/NNS)
(NP the/DT five/CD surviving/VBG workers/NNS)
(NP the/DT latest/JJS week/NN)
(NP six-month/JJ Treasury/NNP bills/NNS)
(NP The/DT average/JJ seven-day/JJ simple/JJ yield/NN)
(NP very/RB modest/JJ amounts/NNS)

NLTK Regular Expression Parsing

 Many types of noun phrases remain

• High scoring regex for all NP chunks

```
(NP Terrence/NNP D./NNP Daniels/NNP)
(NP the/DT National/NNP Cancer/NNP Institute/NNP)
(NP New/JJ York-based/JJ Loews/NNP Corp./NNP)
(NP the/DT highest/JJS)
(NP it/PRP)
(NP who/WP)
(NP who/WP)
(NP that/WDT)
(NP 1997/CD)
(NP 9.8/CD billion/CD)
```

```
NP:

{<DT>?<JJ|JJR|VBN|VBG>*<CD><JJ|JJR|VBN|VBG>*<NNS|NN>+}

{<DT>?<JJS><NNS|NN>?}

{<DT>?<PRP|NN|NNS><POS><NN|NNP|NNS>*}

{<DT>?<NNP>+<POS><NN|NNP|NNS>*}

{<DT|PRP\$>?<RB>?<JJ|JJR|VBN|VBG>*<NN|NNP|NNS>+}

{<WP|WDT|PRP|EX>}

{<DT><JJ>*<CD>}

{<\$>?<CD>+} 6
```

Evaluation

- For evaluation, we need a metric that works at the level of the chunks.
- Precision:
 - The fraction of chunks the system returned that were right
 - "Right" means the boundaries and the label are correct given some labeled test set.
- Recall:
 - The fraction of the chunks that system got from those that it should have gotten.
- F measure: Combination of Precision and Recall