

NLP Lab Session Week 5  
February 13, 2013

## Regular Expressions and Tokenization

So far, we have depended on the NLTK wordpunct tokenizer for our tokenization. Not only does the NLTK have other tokenizers, but we can custom-build our own tokenizer using regular expressions.

Download the examples: LabWeek5examples.txt and rename it as .py from the LabExamples folder or from blackboard.

## Text as Strings

We'll read text from the file emma in the Gutenberg Corpus as before, but just leave it as raw text.

```
>>> import nltk
>>> from nltk import *

>>> file0 = nltk.corpus.gutenberg.fileids( ) [0]
>>> emmatext = nltk.corpus.gutenberg.raw(file0)
```

Remember that this text is a Python string. We'll quickly review some of the operations and functions that are used with strings. (See also section 3.2 in the NLTK book, <http://www.nltk.org/book>.)

Strings can be treated as lists of characters. So if we get the length of a string, it is the number of characters, and if we use indexing with square brackets [ ], we get substrings of characters.

```
>>> type(emmatext)           # type is string
>>> len(emmatext)           # number of characters in the book
>>> shorttext = emmatext[:150] # get the first 150 characters into the variable shorttext
```

If we wanted to do something to every character in the string, we can even loop over the characters; this will print the first 10 characters in the variable shorttext.

```
>>> for char in shorttext[:10]
    print char
```

We use the operator '+' to concatenate strings together.

```
>>> string1 = 'Monty Python'
>>> string2 = 'Holy Grail'
>>> string1 + string2
>>> string1 + ' and the ' + string2
```

Also check out Table 3.2 to see other string functions. For example, we could use the function `replace` to replace all the new characters `'\n'` with a space `' '`.

```
>>> newemmatext = emmatext.replace('\n', ' ')
>>> shorttext = newemmatext[:150]
>>> shorttext
```

We have redefined the variable `shorttext` to be the first 150 characters without newlines.

## Regular Expressions for Tokenizing Text

In the NLTK book, section 3.4 is about regular expressions, including Table 3.3 with basic regular expression patterns, and section 3.7 includes Table 3.4 with regular expression symbols.

Let's start our investigation of using regular expressions to tokenize text by looking at some simple patterns first. We'll start with a pattern for words that just finds alphabetic characters. There are several functions in the module `re` for finding how patterns match text, e.g. `re.match` finds any match at the beginning of a string, `re.search` finds a match anywhere in the string, and `re.findall` will find the substrings that matched anywhere in the string.

```
>>> import re
>>> pword = re.compile('\w+')
>>> re.findall(pword, shorttext)
```

This does fine on the alphabetic words of this simple text, noting that it ignores the number 1816, so let's get an example of text with some special characters to illustrate some other situations.

```
>>> specialtext = 'That U.S.A. poster-print costs $12.40, but with 10% off.'
>>> re.findall(pword, specialtext)
```

Getting only alphabetic text leaves lots of the string unmatched. Let's start making a more general regular expression to match tokens by matching words can have an internal hyphen. In this case, we need to put parentheses around the part of the pattern that can be repeated 0 or more times. Unfortunately, `findall` will then only report the part that matched inside those parentheses, so we'll put an extra pair of parentheses around the whole match.

```
>>> ptoken = re.compile('(\w+(-\w+)*)')
>>> re.findall(ptoken, specialtext)
```

`re.findall` has reported both the whole matched text and the internal matched text. We could fix this by using the `re.groups` function to access only the outer match, but instead we'll just ignore this for now while we're developing regular expressions. NLTK provides a more elegant way to represent the regular expressions later.

Now we try to make a pattern to match abbreviations that might have a `'.'` inside, like U.S.A. We only allow capitalized letters.

```
>>> pabbrev = re.compile('([A-Z]\.+)')
>>> re.findall(pabbrev, specialtext)
```

This worked well, so let's combine it with the words pattern to match either words or abbreviations.

```
>>> ptoken = re.compile('\w+(-\w+)*|([A-Z]\.+)')
>>> re.findall(ptoken, specialtext)
```

Well, that didn't work because it first found the alphabetic words which found 'U', 'S' and 'A' as separate words before it could match the abbreviations. So the **order of the matching patterns really matters** if an earlier pattern matches part of what you want to match. We can switch the order of the token patterns to match abbreviations first and then alphabets.

```
>>> ptoken = re.compile('([A-Z]\.+)|\w+(-\w+)*')
>>> re.findall(ptoken, specialtext)
```

That worked much better. Now we'll add an expression to match the currency, and we'll put an 'r' in front of the string, Python's notation for a raw string. This accepts '\ ' as itself in a string.

```
>>> ptoken = re.compile(r'([A-Z]\.+)|\w+(-\w+)*|\$?\d+(\.\d+)?')
>>> re.findall(ptoken, specialtext)
```

We can keep on adding expressions, but the notation is getting awkward. We can make a prettier regular expression that is equivalent to his one by using Python's triple quotes (works for either "" or '' ) that allows a string to go across multiple lines without adding a newline character. And we also use the regular expression verbose flag to allow us to put comments at the end of every line, which the re compiler will ignore.

```
ptoken = re.compile(r"([A-Z]\.+)      # abbreviations, e.g. U.S.A.
                    | \w+(-\w+)*    # words with internal hyphens
                    | \$?\d+(\.\d+)? # currency, like $12.40
                    ", re.X)        # verbose flag
```

But we still had to put in extra parentheses for the findall function, which messed up the output a lot. So NLTK has provided us with an even better way to write these expressions.

### Regular Expression Tokenizer using NLTK Tokenizer

(From section 3.7 in the NLTK book <http://www.nltk.org/book> )

NLTK has built a tokenizing function that helps you write tokenizers by giving it the compiled pattern. Regular expressions can also be written down in the "verbose" version, using the (?x) flag that allows the alternatives to be on different lines with comments, and it also alleviates the need to put extra parentheses.

```
pattern = r''' (?x)          # set flag to allow verbose regexps
```

```

([A-Z]\.)+          # abbreviations, e.g. U.S.A
| \w+(-\w+)*       # words with internal hyphens
| \$?\d+(\.\d+)?%?  # currency and percentages, $12.40, 50%
| \.\.\.           # ellipsis
| [[\.,;"'()?():-_' ] # separate special character tokens
, ,

```

As far as I can tell, the nltk function `regexp_tokenize` applies these regular expressions to text by applying each regular expression in order to get anything that matches as a token. We observed the importance of the order of expressions earlier, but also note that it is important that the expression to separate special characters as individual tokens comes last in the list, so that other expressions, such as the words with internal hyphens, can first get longer tokens that involve individual characters.

We put this pattern into NLTK's function for a regular expression tokenizer. Note the order of the arguments to this function; first give the text and then the pattern.

```

>>> nltk.regexp_tokenize(shorttext], pattern)
>>> nltk.regexp_tokenize(specialtext, pattern)

```

Note that if there are any characters not matched by one of the regular expression patterns, then it is omitted as a token in the result. (For some reason, the % is being ignored, and I didn't have time to debug it.)

Next, we'll try to make a regular expression tokenizer appropriate for tweet text. Some of the patterns in this tokenizer are taken from `tweetmotif`, a Python regular expression tokenizer written for tweets by Brendan O'Connor (<http://tweetmotif.com/about>). Here is a tokenizer:

```

tweetPattern = r''' (?x)          # set flag to allow verbose regexps
    (https?://|www)\S+          # simple URLs
    | (:-\)|;-\))              # small list of emoticons
    | &(amp|lt|gt|quot);       # XML or HTML entity
    | \#\w+                    # hashtags
    | @\w+                     # mentions
    | \d+:\d+                  # timelike pattern
    | \d+\.\d+                 # number with a decimal
    | (\d+,)+?\d{3}(?=[^,]|$)) # number with a comma
    | ([A-Z]\.)+              # simple abbreviations
    | (--+)                   # multiple dashes
    | \w+(-\w+)*              # words with internal hyphens or apostrophes
    | ['\".?!,,:;]+          # special characters
, ,

```

We need some examples to work with (be sure and get these examples from `LabWeek5examples.py`.)

```

tweet1 = "@natalieohayre I agree #hc09 needs reform- but not by crooked politicians who r
clueless about healthcare! #tcot #fishy NO GOV'T TAKEOVER!"

```

```

tweet2 = "To Sen. Roland Burris: Affordable, quality health insurance can't wait
http://bit.ly/j63je #hc09 #IL #60660"

```

```
tweet3 = "RT @karoli: RT @Seriou: .@whitehouse I will stand w/ Obama on #healthcare, I trust him. #p2 #tlot"
```

Try the regexp tokenizer on these tweets, for example:

```
nlTK.regex_tokenize(tweet1,tweetPattern)
```

### Exercise

Choose one of the following, i.e. work with either the regular pattern or the tweet pattern in the tokenizer. You may work in groups.

1. Run the regexp tokenizer with the regular pattern on the sentence “Mr. Black and Mrs. Brown attended the lecture by Dr. Gray, but Gov. White wasn’t there.”
  - a. Design and add a line to the pattern of this tokenizer so that titles like “Mr.” are tokenized as having the dot inside the token. Test and add some other titles to your list of titles.
  - b. Design and add the pattern of this tokenizer so that words with a single apostrophe, such as “wasn’t” are taken as a single token.

OR

2. Run the regexp tokenizer with the tweet pattern on the three example tweets.
  - a. Design and add a line to the pattern of this tokenizer so that titles like “Sen.” and “Rep.” are tokenized as having the dot inside the token. Test and add some other titles to your list of titles.
  - b. Design and add to the pattern of this tokenizer so that words with a single apostrophe, such as “can’t” are taken as a single token.
  - c. Design and add to the pattern of this tokenizer so that the abbreviation “w/” is taken as a single token.

Choose at least one of your tokenizer solutions and post your revised pattern to the Discussion in the iLMS for Week 5 with a short example text that demonstrates its effect. Mention any examples that you think of that need additional regular expressions to be tokenized.